

— Main order —

1. Base model : P257 (Safety pattern type pressure gauge)
2. Nominal diameter (mm)
  - ☐ 2 : 63 ☐ 4 : 100
3. Type of mounting
  - ☐ G : Lower back connection, direct
4. Accuracy
  - ☐ 2 :  $\pm 0.5\%$  of full scale.(Not available with diameter 63mm)
  - ☐ 3 :  $\pm 1.0\%$  of full scale.(Not available with diameter 63mm)
  - ☐ 4 :  $\pm 1.6\%$  of full scale.(Only available with diameter 63mm)
5. Process connection
  - ☐ B : 1/8"
  - ☐ C : 1/4"
  - ☐ D : 3/8", not available with diameter 63 mm
  - ☐ E : 1/2", not available with diameter 63 mm

6. Connection type

- ☐ B : PF ☐ C : PT ☐ D : NPT
- ☐ F : BSPT ☐ G : BSP (G)

7. Unit

- ☐ H : bar ☐ I : MPa
- ☐ J : kPa ☐ Z : Other \_\_\_\_\_

8. Range

XXX : Refer to pressure unit and range table

9. Pressure connection material and dial color

- ☐ 3 : 316SS and 2 colors
- ☐ 4 : 316L SS and 2 colors
- ☐ 7 : 316SS and 3 colors
- ☐ 8 : 316L SS and 3colors
- ☐ Z : Monel

10. Option

- ☐ 0 : None
- ☐ 1 : Accessories
- ☐ 8 : Silicone filling
- ☐ 9 : Glycerin filling

— Standard specifications—

11. Working pressure

Steady : 75% of full scale (63 mm)

100% of full scale (100 mm)

Over range protection : 130% of full scale

12. Working temperature

Ambient :  $-40 \sim 65^{\circ}\text{C}$

$-20 \sim 65^{\circ}\text{C}$  (With glycerin filling)

$-40 \sim 65^{\circ}\text{C}$  (With silicone filling)

Fluid : Max.  $200^{\circ}\text{C}$

Max.  $100^{\circ}\text{C}$  (With glycerin filling)

Max.  $100^{\circ}\text{C}$  (With silicone filling)

13. Degree of protection

EN60529/IEC529/IP67

14. Element type : Bourdon tube

15. Mat'l

- 1) Case & Cover : Stainless steel (304SS)
- 2) Element : Stainless steel (316SS)
- 3) Process connection : Stainless steel (316SS)
- 4) Movement : Stainless steel
- 5) Windows : Safety glass

16. Dimension


Dial size	A	B	D		E		F	
			S.T.D	External	S.T.D	External	S.T.D	External
63	64	62	42.5	-	70	-	16.7	-
100	101.3	99	59	61	98.5	100.5	29	

This drawing and the specifications are the intellectual property of WISE CONTROL INC. therefore, without a prior written consent from WISE CONTROL INC., it is strictly prohibited to reproduce the drawing or manufacture the identical products according to its specifications provided here.

Unless otherwise specified

Decimal dimensions  $\pm 5$   
Angle dimensions  $\pm 1^{\circ}$   
Dimensions are in millimeter

THIRD ANGLE PROJECTION



**WISE**<sup>®</sup>

WISE Control Inc.

	SIGNATURE	DATE
PREPARED BY	K.S.LEE	18.06.01
REVIEWED BY	J.S.PARK	18.06.01
APPROVED BY	D.M.CHO	18.06.01
REV. NO.	0	

DRAWING TITLE :	"G" TYPE (LIQUID FILLED)
	SOLID FRONT SAFETY PRESSURE GAUGE
DWG NO.	P257XXXG-S.T.D
SCALE : N/S	W.T.
	SHEET OF

— Sample ordering code —

1	2	3	4	5	6	7	8	9	10
P257	4	G	3	C	D	H	XXX	3	9

2						
1						
NO	REASON	DATE	PREPARED BY	CHECKED BY	APPROVED BY	

REVISION