

## - Main order -

1. Base model : P336 (Duplex pressure gauge, round type)

2. Nominal diameter (mm)

☐ 4 : 100, round type

3. Type of mounting

☐ G Low back connection, direct

4. Accuracy

☐ 4 :  $\pm 1.5\%$  of full scale.

5. Process connection

☐ D : 3/8"

6. Connection type

☐ B : PF

7. Unit

☐ H : bar ☐ I : MPa ☐ J : kPa

8. Range

☐ 044 : 0 ~ 0.4 MPa ☐ 045 : 0 ~ 0.6 MPa☐ 047 : 0 ~ 1.0 MPa ☐ 050 : 0 ~ 1.5 MPa☐ 051 : 0 ~ 2.0 MPa ☐ 052 : 0 ~ 2.5 MPa☐ 054 : 0 ~ 3.5 MPa

9. Dial color

☐ 2 : 2 colors☐ 7 : 3 colors

10. Option

☐ 0 : None☐ 1 : Accessories☐ 4 : Orifice☐ 5 : Accessories and Orifice

## - Standard specifications -

11. Working pressure

Steady : 75% of full scale

Over range protection : 130% of full scale

12. Working temperature

Ambient :  $-40 \sim 65^{\circ}\text{C}$ Fluid : Max.  $200^{\circ}\text{C}$ 

13. Element type : Bourdon tube

14. Mat'l

1) Case &amp; Cover : Black painted aluminium

2) Element : Stainless steel (316SS)

3) Process connection : Stainless steel (316SS)

4) Movement : Brass

5) Windows : Safety glass

## - Sample ordering code -

1	2	3	4	5	6	7	8	9	10
P336	4	G	4	D	B	I	047	2	0

2						
1						
NO	REASON	DATE	PREPARED BY	CHECKED BY	APPROVED BY	


## REVISION

This drawing and the specifications are the intellectual property of WISE CONTROL INC. therefore, without a prior written consent from WISE CONTROL INC., it is strictly prohibited to reproduce the drawing or manufacture the identical products according to its specifications provided here.

## Unless otherwise specified

Decimal dimensions  $\pm 0.05$   
 Angle dimensions  $\pm 1^{\circ}$   
 Dimensions are in millimeter

## THIRD ANGLE PROJECTION



	SIGNATURE	DATE
PREPARED BY	K.S.LEE	18.06.01
REVIEWED BY	J.S.PARK	18.06.01
APPROVED BY	D.M.CHO	18.06.01
REV. NO.	0	

**WISE**<sup>®</sup>

WISE Control Inc.

 DRAWING TITLE :  
 "G" Type  
 Duplex pressure gauge

 DWG NO.  
 P336100G-S.T.D

SCALE : N/S    W.T.    SHEET OF