

— Main order —

1. Base model : P428 (Screwed process connection diaphragm)
2. Nominal diameter (mm)
 - ☐ XA : 100 ☐ XB : 150
3. Upper flange and diaphragm material
 - ☐ B : 304SS and 316L SS
 - ☐ H : 304SS and 316L SS + PTFE Sheet
 - ☐ J : 316SS and 316L SS
 - ☐ Q : 316SS and 316L SS + PTFE Sheet

— Sample ordering code —

1	2	3	4	5	6	7	8
P428	XA	B	XXX	J	XXX	BX	0


2						
1						
NO	REASON	DATE	PREPARED BY	CHECKED BY	APPROVED BY	

REVISION

This drawing and the specifications are the intellectual property of WISE CONTROL INC. therefore, without a prior written consent from WISE CONTROL INC., it is strictly prohibited to reproduce the drawing or manufacture the identical products according to its specifications provided here.

Unless otherwise specified
 Decimal dimensions ± 5
 Angle dimensions $\pm 1^\circ$
 Dimensions are in milli meter

THIRD ANGLE PROJECTION



	SIGNATURE	DATE
PREPARED BY	K.S.LEE	18.06.01
REVIEWED BY	J.S.PARK	18.06.01
APPROVED BY	D.M.CHO	18.06.01
REV. NO.	0	

WISE[®]
 WISE Control Inc.

	DRAWING TITLE : DIAPHRAGM SEAL SCREWED TYPE LOW P/G		
	DWG NO. P428XXXX-S.T.D		
	SCALE : N/S	W.T.	SHEET OF

4. Process connection type
 XXX : Refer to process connection type table
5. Unit
☐ J : kPa ☐ S : mbar
6. Range
 XXX : Refer to pressure unit and range table
7. Unit flange material
 - ☐ BX : 304SS
 - ☐ CX : 316SS
 - ☐ EX : 316L SS
 - ☐ 51 : 316L SS + coating
 - ☐ RX : 304SS + coating
 - ☐ SX : 316SS + coating
 - ☐ ZZ : Other
8. Option
 - ☐ 0 : None
 - ☐ 1 : Accessories
 - ☐ 4 : Electropolished under flange

— Standard specifications —

11. Accuracy : $\pm 1.5\%$ of full scale
12. Working temperature
 Ambient : $-20 \sim 65^\circ\text{C}$
 Fluid : Max. 100°C
13. Element type : Diaphragm
14. Mat'l
 - 1) Upper flange (Gauge side) : Stainless steel (304SS, 316SS)
 - 2) Diaphragm : 316L SS
 - 3) Under flange (Process side)
 : Stainless steel (304SS, 304L SS, 316SS, 316L SS)
 Monel, Hastelloy-C

15. Dimension

	A	B	C (ONLY 100mmH ₂ O)	E	F
100mm	111	100	100 (140)	60	13.7
150mm	150.6	153.4	100 (140)	60	27