

JUMO miroVIEW

Smart digital indicator with limit value monitoring function for panel mounting



The features at a glance

- Flexible application in panel mounting including limit value monitoring
- Clear text-supported operation, parameterization, configuration in 4 device languages
- Visualization of process information via message texts
- Convenient quick configuration via USB interface
- Retrofit of mechanical dial thermometers and contact dial thermometers possible



Brief overview

The JUMO miroVIEW – as a smart digital indicator with limit value monitoring function – is suitable for flexible application in panel building. This device has measurement inputs for RTD temperature probes, thermocouples, or standard signals. It offers an alternative solution for mechanical dial thermometers or contact dial thermometer, especially in the round installation format (60 mm and 80 mm).

Other advantages

- ▶ Intuitive startup and operation
- ▶ Integrated timer function, service and operating hours counter
- ▶ Fast wiring through PUSH IN technology
- ▶ Cost-effective solution for individual display functions
- ▶ Available in round and square housing design

Technical data

Product name	JUMO miroVIEW
Type	701580, 701590, 701591
Measurement inputs	RTD temperature probes, thermocouples, or standard signals
Outputs	Up to 2 relays
Voltage supply	AC 230 V, +10/-15 %, 48 to 63 Hz, AC 115 V, +10/-15 %, 48 to 63 Hz, DC 12 to 24 V +15/-15 %
Formats	701580: (76 × 36 × 62) mm 701590: (∅ 60 × 80) mm 701591: (∅ 80 × 80) mm
Approvals	UL