













Dial Thermometer - Industrial Version (608002)

- Bimetal measuring system
- Stainless steel case
- Class 1
- Impervious to ambient temperature



Order details

(1) Basic type		
608002/0110	Dial thermometer, industrial version, class 1, model 01, housing size \varnothing 100 mm	
608002/0160	Dial thermometer, industrial version, class 1, model 01, housing size \varnothing 60 mm	
608002/0180	Dial thermometer, industrial version, class 1, model 01, housing size \varnothing 80 mm	
608002/1810	Dial thermometer, industrial version, class 1, model 18, housing size \varnothing 100 mm	
608002/1860	Dial thermometer, industrial version, class 1, model 18, housing size \varnothing 60 mm	
608002/1880	Dial thermometer, industrial version, class 1, model 18, housing size \varnothing 80 mm	
(2) Indication range		
357	-50...+50 °C	
469	-40...+40 °C	
632	-20...+60 °C	
643	-20...+120 °C	
810	0...80 °C	
814	0...100 °C	
818	0...120 °C	
832	0...200 °C	
834	0...250 °C	
840	0...300 °C	
848	0...400 °C	
854	0...500 °C	
(3) Process connection		
010	TA01, immersion tube with shoulder	
018	TA08, immersion tube with sliding mounting plate of plated steel + fixing screw	
820	SH09, weld-in pocket with clip and fixing screw for TF01	
841	TA04/05, immersion tube with fixed hexagon	
844	TA02/TF05, immersion tube with union nut & screw	
845	TA03/TF05, immersion tube with union nut	
847	TA06/TF05, sliding clamp fitting on support tube	
858	SH04, screw-in pocket as per DIN 43772 CE	

891	SH05/TF01, screw-in pocket, assembled	
913	SH07, screw-in pocket, assembled, with clip and fixing screw	
(4) Diameter		
10	10 mm	
12	12 mm	
14	14 mm	
17	17 mm	
6	6 mm	
(5) Thread		
000	Without thread	
103	G3/8 thread	
104	G1/2 thread	
105	G3/4 thread	
144	1/2-14NPT thread	
(6) Material of probe /		
26	CrNi 1.4571	
(7) Process connection material		
26	CrNi 1.4571	
(8) Insertion length		
100,00	100mm	
150,00	150mm	
200,00	200mm	
(9) Extra codes		
000	Without extra code	
404	Protection IP65	
430	Drag indicator	
522	Customized scale	

Order code

(1) (2) (3) (4) (5) (6) (7) (8) (9)
 - - - - - - - /


Stock versions

Order code	Indication range	Diameter	Thread	Insertion length	Part no.
608002/0180-818-847-6-104-26-26-200/000	0...120 °C	6 mm	G1/2 thread	200mm	80001185
608002/0180-834-847-6-104-26-26-200/000	0...250 °C	6 mm	G1/2 thread	200mm	80001186

Accessories see price sheet:

- Process Connections for Dial Thermometers (608730)