



Dial Thermometer – Transformer Version (608005)

- Bimetal measuring system
- Stainless steel case
- Drag indicator
- Impervious to ambient temperature



Order details

(1) Basic type		
608005/1080	Dial thermometer, transformer version, model 10, housing size ø 80 mm	
(2) Indication range		
643	-20...+120 °C	
818	0...120 °C	
(3) Process connection		
874	TA24, immersion tube with screw, O seal and fixing screw	
(4) Diameter prot. tube		
8,00	8 mm	
(5) Thread		
104	G1/2 thread	
105	G3/4 thread	
106	G1 thread	
(6) Process connection material		
97	Stainless steel (CrNi, 14571) probe / brass (CuZn) screw	
(7) Insertion length		
150,00	150mm	
(8) Extra codes		
000	Without extra code	
409	Housing and front ring to be polished	
434	Drag indicator, adjustable with screwdriver, protected by cover	
522	Customized scale	

Order code

(1) (2) (3) (4) (5) (6) (7) (8)
 - - - - - - /

Attention! Order quantity and packaging unit per version = 3 pieces for stock versions.



Stock versions

Order code	Indication range	Thread	Extra code 430	Part no.
608005/1080-643-874-8-106-97-150/430,522,	-20...+120 °C	G1 thread	Drag indicator	00483589

Accessories see price sheet:

- Process Connections for Dial Thermometers (608730)