

JUMO dicoTEMP 800 - Dial Thermometer with Microswitch (608530)

- Low mounting depth
- Class 1.5
- Display range -50 to +500 °C
- Temperature controller with actual value display as panel mounting device in a stainless steel case
- 1 microswitch
- Case size Ø 80 mm



Order details

(1) Basic type	
608530	DicoTEMP 800
(2) Basic type extension	
2060	Design typ 20 case size 60 mm
2080	Design typ 20 case size 80 mm
2160	Design typ 21 case size 60 mm
2180	Design typ 21 case size 80 mm
(3) Indication range	
818	0...120 °C
834	0...250 °C
926	50...250 °C
927	50...300 °C
(4) Contact rating	
11	AC/DC 24V, 0,1A
26	AC 230V, 5(1,5)A, cos = 1(0,6)
27	AC 230V, 10(3)A, cos = 1(0,6)
(5) Capillary version	
17	FL17, stainless steel capillary, ø 1.5 mm
21	FL21, copper capillary, ø 1.0 mm
22	FL22, stainless steel capillary, ø 1.0 mm
(6) Capillary length	
1000	1,000 mm
2000	2,000 mm
(7) Process connection	
750	TF01, temperature probe with stepped support tube
848	TA25/TF11, sliding clamp fitting on capillary
(8) Diameter	
6	6 mm
8	8 mm
(9) Thread	
000	Without thread
103	G3/8 thread
104	G1/2 thread
(10) Material of probe /	
26	CrNi 1.4571
96	copper probe / brass support tube
(11) Process connection material	
00	Without process connection
26	CrNi 1.4571
46	CuZn (brass)
(12) Insertion length	
0,00	Min. insertion length TF11
50,00	50 mm
100,00	100 mm
(13) Switching output	
20	SA20, one micro switch
(14) Extra codes	

000	Without extra code
518	Setpoint stop minimum / maximum, factory settings
520	Fixed switching point, factory settings
522	Customized scale

Order code

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12) (13) (14)
 / - - - - - - - - - - - - /

Quantity discount:

As of 3 pieces: 5 %

As of 5 pieces: 10 %

As of 10 pieces: 20 %

As of 25 pieces: please inquire

Stock versions

Order code	Indication range	Part no.
608530/2180-926-26-22-2000-848-6-171-26-26-0-20/000	50...250 °C	00669249