

LR 316 - Laboratory controller in a desk-top case (700703)

- Wired ready for use
- 2-state controller
- Pt100, Pt1000, Fe-CuNi "L" or NiCr-Ni "K"
- Load circuit up to 16A
- Modbus port



Order details

(1) Basic type	
700703/10	LR 316 laboratory controller (2-state controller inverse)
700703/11	LR 316 laboratory controller (2-state controller direct)
(2) Input	
042	Fe-CuNi "L" / Pt100 / Pt1000 (Pt100 adjusted)
043	Ni-CrNi "K" / Pt100 / Pt1000 (Pt100 adjusted)
(3) Output	
101	Via relay (NO contact) and built-in socket (I max. 16 A)
105	Via solid state relay and built-in socket (I max. 10 A)
(4) Voltage supply	
35	AC230V +10/-10%,50Hz
(5) Extra codes	
000	Without extra code
053	Interface RS422/485

Order code

(1) (2) (3) (4) (5)
 - - - /

Stock versions

Order code	Part no.
700703/10-042-101-35/000	00453168
700703/10-042-105-35/000	00474651

Accessories see price sheet:

- Mineral-Insulated Thermocouple with Bare Connection Wires According to DIN 43710 and DIN EN 60584 (901210)
- Mineral-Insulated RTD Temperature Probes with Bare Connection Wires According to DIN EN 60751 (902210)