

JUMO miroVIEW – Smart Digital Indicator with Limit Value Monitoring

- Integrated timer function
- Service and operating hours counter
- Bluetooth (option)
- Fast wiring through pluggable terminal strips with PUSH IN technology
- High-quality display and intuitive operation
- Configuration on the device or with the setup program (accessories) through USB interface (USB powered)
- Operator guidance with text support in 4 languages
- Limit value monitoring function



Order details

(1) Basic type	
701590	JUMO miroVIEW with 1 relay, size Ø 60 x 80 mm
701591	JUMO miroVIEW with 1 relay, size Ø 80 x 80 mm
(2) Version	
0	Standard version
2	Customer-specific software
(3) Input	
01	1 RTD temperature probe Pt100, Pt1000 in 2-wire circuit, 1 digital input
(4) Output	
25	1 relay (NO contact AC 250 V, 16 A) resistive load
(5) Voltage supply	
02	AC 230 V +10 / -15 %, 48...63 Hz
05	AC 115 V +10 / -15 %, 48...63 Hz
30	DC 12 to 24 V +15/-15 %

Order code

(1) (2) (3) (4) (5)
 / - - -

Stock versions

Order code	Part no.
701590/0-01-25-02/000	30047410
701591/0-01-25-02/000	30047413

Accessories

Description	Part no.
USB cable, A connector to Micro-B connector length 3 m	00616250

Software

Description	Part no.
Setup JUMO miroTRON/miroVIEW	00777355