

Hygienic Thermowells for Temperature Probes Used in the Food and Pharmaceutical Industry (902812)

- Rapid response times
- Hygienic process connections
- Reduced servicing and maintenance costs
- Fast and unlimited exchange of the temperature probe
- Easy cleaning
- High process reliability



Order details

(1) Basic type	
902812/10	Hygienic thermowell for temperature probes in the food and pharmaceutical industry with internal screw thread M 14 x 1
(2) Diameter prot. tube	
6,00	6 mm
(3) Insertion length	
50,00	50 mm
100,00	100 mm
150,00	150 mm
(4) Process connection	
000	Without process connection
103	Screw connection G 3/8
104	Screw connection G 1/2
380	Screw connection G 1/2 with CIP-compliant conical seal
400	Welding sleeve
550	DN 20 aseptic DIN 11864-1A
551	DN 25 aseptic DIN 11864-1A
552	DN 32 aseptic DIN 11864-1A
553	DN 40 aseptic DIN 11864-1A
554	DN 50 aseptic DIN 11864-1A
601	Taper socket with union nut DN 10 DIN 11851 (dairy compression fitting)
604	Taper socket with union nut DN 25 DIN 11851 (dairy compression fitting)
605	Taper socket with union nut DN 32 DIN 11851 (dairy compression fitting)
611	Clamping socket (clamp) DN 10/20 DIN 32676
613	Clamping socket (clamp) DN 25/32/40 DIN 32676 (1 1/2" ISO 2852)
616	Clamping socket (Clamp) DN 50 DIN 32676 (2" ISO 2852)
617	Clamping socket (clamp) 2 1/2" similar to DIN 32676
681	Ball welding socket with threaded fitting
684	VARIVENT connection DN 15/10
685	VARIVENT connection DN 32/25
686	VARIVENT connection DN 50/40
755	BioControl D25 (NEUMO)
756	BioControl D50 (NEUMO)
757	BioControl D65 (NEUMO)
758	BioControl D80 (NEUMO)
840	Ball welding sleeve (material 316 Ti)
(5) Protection tube material	
24	Stainless steel 316 L (material-no. 1.4404)
(6) Extra codes	
000	Without extra code
374	Inspection certificate 3.1 DIN EN 10204 material
458	Wetted, electrolytically polished parts, surface roughness Ra <= 0.4 µm
810	Welding socket (only for process connection 380)

Order code

(1) (2) (3) (4) (5) (6)
 - - - - /

Quantity discounts upon request

