

## JUMO MIDAS DR – OEM Cabinet Pressure Transmitter (401009)

Application: pneumatics/switch cabinet mounting

- 0 to 1.6 bar – 0 to 16 bar relative
- Elastomer seal
- Compact design: as of 45 mm in length



### Order details

<b>(1) Basic type</b>	
401009/000	JUMO MIDAS DR
<b>(2) Input</b>	
455	0 to 1.6 bar relative pressure
456	0 to 2.5 bar relative pressure
457	0 to 4 bar relative pressure
458	0 to 6 bar relative pressure
459	0 to 10 bar relative pressure
460	0 to 16 bar relative pressure
479	-1 to 0.6 bar relative pressure
480	-1 to 1.5 bar relative pressure
481	-1 to 3 bar relative pressure
482	-1 to 5 bar relative pressure
483	-1 to 9 bar relative pressure
484	-1 to 15 bar relative pressure
999	Special measuring range relative pressure
<b>(3) Output</b>	
405	4 to 20 mA 2-wire
412	0.5 to 4.5 V 3-wire
415	0 to 10 V 3-wire
418	1 to 5 V 3-wire
420	1 to 6 V 3-wire
<b>(4) Process connection</b>	
383	Plug-in screw connection for Rohr/Schlauch 6 x 4, DN 6
547	Rp 1/8 female
<b>(5) Housing material</b>	
20	CrNi (stainless steel)
<b>(6) Seal</b>	
601	FPM
<b>(7) Electrical connection</b>	
06	Screw terminal

### Order code

(1) (2) (3) (4) (5) (6) (7)  
 -  -  -  -  -  -

### Important information about the order details

#### Process connection 383

Only negative overpressure (negative pressure) up to -0.95 bar can be achieved, not -1.

Minimum order quantity for production orders:

4 pieces

