

JUMO dTRANS p32 - Pressure Transmitter (402051)

Feature: for dry, non-corrosive, and non-ionizing gaseous media

- 0 to 40 mbar up to 0 to 600 mbar relative
- Protection type: IP65/IP67



Order details

(1) Basic type	
402051/000	JUMO dTRANS p32
402051/034	JUMO dTRANS p32 sensor with gel template
(2) Input	
411	0 to 40 mbar relative pressure
413	0 to 60 mbar relative pressure
414	0 to 100 mbar relative pressure
415	0 to 160 mbar relative pressure
451	0 to 0.25 bar relative pressure
452	0 to 0,4 bar relative pressure
453	0 to 0.6 bar relative pressure
999	Special measuring range relative pressure
(3) Output	
405	4 to 20 mA 2-wire
415	0 to 10 V 3-wire
(4) Process connection	
501	G 1/8 DIN EN 837
502	G 1/4 DIN EN 837
504	G 1/2 DIN EN 837
511	1/4-18NPT DIN EN 837
512	1/2-14NPT DIN EN 837
523	G 1/2 DIN 3852-11
692	Hose connection 6 mm
(5) Process connection material	
20	CrNi (stainless steel)
(6) Electrical connection	
12	Fixed connecting cable encapsulated
36	Round plug M12 × 1
61	Connector for cable connection DIN EN 175301-803, form A

Order code

(1) (2) (3) (4) (5) (6)
 - - - - -



Accessories

Description	Part no.
Line socket 4-pole, M12×1, straight, 2 m	00404585
Line socket 4-pole, M12 × 1, angled, 2 m	00409334
Line socket 4-pole, M12×1, pressure comp Buchse	00512341
Calibration of the mechanical measurand, pressure on site (also DAkkS)	00758363