

## JUMO CANtrans p Ceramic - Pressure Transmitter with CANopen Output (402055)

- 0 to 1.6 bar up to 0 to 100 bar relative
- Linearized, temperature-compensated
- Elastomer-sealed
- Temperature of medium: -20 to +85 °C



### Order details

<b>(1) Basic type</b>	
402055/000	JUMO CANtrans p ceramic
<b>(2) Input</b>	
455	0 to 1.6 bar relative pressure
456	0 to 2.5 bar relative pressure
457	0 to 4 bar relative pressure
458	0 to 6 bar relative pressure
459	0 to 10 bar relative pressure
460	0 to 16 bar relative pressure
461	0 to 25 bar relative pressure
462	0 to 40 bar relative pressure
463	0 to 60 bar relative pressure
479	-1 to 0.6 bar relative pressure
480	-1 to 1.5 bar relative pressure
481	-1 to 3 bar relative pressure
482	-1 to 5 bar relative pressure
483	-1 to 9 bar relative pressure
484	-1 to 15 bar relative pressure
434	-1 to 16 bar relative pressure
485	-1 to 24 bar relative pressure
999	Special measuring range relative pressure
<b>(3) Output</b>	
450	CANopen
<b>(4) Process connection</b>	
502	G 1/4 DIN EN 837
511	1/4-18NPT DIN EN 837
521	G 1/4 DIN 3852-11
523	G 1/2 DIN 3852-11
<b>(5) Process connection material</b>	
20	CrNi (stainless steel)
<b>(6) Seal</b>	
601	FPM
604	FFPM
<b>(7) Electrical connection</b>	
36	Round plug M12 × 1

### Order code

(1) (2) (3) (4) (5) (6) (7)  
 -  -  -  -  -  -



**Accessories**

Description	Part no.
PC-CAN-interface for USB-interface	00449941
BUS termination resistor CAN- Bus/digiLi	00461591