

Pressure Separator with ISS/SMS/RJT Socket and (Grooved) Union Nut (409778)

- Pressure separator with ISS hexagon nut
- Pressure separator with SMS socket and grooved union nut
- Pressure separator with RJT socket and union nut
- Process connection DN 1", DN 1 1/2", DN 2" (PN 40)



Order details

(1) Basic type	
409778/00	Pressure separator with ISS hexagon nut or SMS or RJT nozzle with grooved union nut
(2) Process connection	
577	RJT DN 1
578	RJT DN 1 1/2
579	RJT DN 2
584	SMS DN 1
585	SMS DN 1 1/2
586	SMS DN 2
587	ISS DN 1
588	ISS DN 1 1/2
589	ISS DN 2
(3) Nominal pressure	
040	PN40
(4) Process connection material	
20	CrNi (stainless steel)
99	According to customer specifications

Order code

(1) (2) (3) (4)
 - - -

Additional prices

Capillary tube

	Price EUR
Integrated cooling element	102.45
1.00 m capillary tube	153.67
1.50 m capillary tube	167.90
2.00 m capillary tube	182.12
3.00 m capillary tube	210.59
5.00 m capillary tube	267.47

Important information about order details and further price quotations

Filling medium

The pressure separators are filled with silicone oil (standard).

Special / customer version

Please specify, if necessary, the requested special filling medium and the length of the capillary tube in plain text.

