


**Panel-Mounted Thermostats, ETH Series (602010)**

- Liquid expansion
- Microswitch


**Order details**

<b>(1) Basic type</b>	
602010	Panel-mounting thermostat, ETH series
<b>(2) Basic type extension</b>	
20	ETH-20 safety temperature monitor STW
70	ETH-70 safety temperature limiter STB
<b>(3) Control range 1</b>	
043	20...150 °C
045	20...400 °C
046	20...500 °C
052	30 to 110 °C
063	50...250 °C
064	50...300 °C
066	60...130 °C
<b>(4) Switching differential</b>	
00	Without switching differential
20	2 %
50	5 %
70	7 %
90	9 %
<b>(5) Capillary length</b>	
1000	1000 mm
2000	2000 mm
3000	3000 mm
4000	4000 mm
5000	5000 mm
<b>(6) Material of capillary</b>	
20	CrNi (stainless steel)
40	Cu (copper)
<b>(7) Process connection</b>	
10	Plain cylindrical probe
20	Screw-in thermowell
<b>(8) Thread</b>	
00	Without thread
13	G 1/2
<b>(9) Process connection material</b>	
00	Without process connection
20	CrNi (stainless steel)
46	CuZn (brass)
<b>(10) Fitting length</b>	
000	Without pocket
100	100 mm
120	120 mm
150	150 mm
200	200 mm
300	300 mm
<b>(11) Immersion tube diameter</b>	



00	Without thermowell
10	10 mm
8	8 mm
<b>(12) Probe diameter</b>	
6	6 mm
8	8 mm
<b>(13) Extra codes</b>	
000	Without extra code
574	Microswitch with opening contact, restart lock and additional signal contact (only for STB)
702	Snap action contact with gold-plating

**Order code**

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12) (13)  
 /  -  -  -  -  -  -  -  -  -  -  -  -


**DGRL**


Accessories see price sheet:

- Process Connections for Thermostats (606710)