

## JUMO diraVIEW 104/108/116/132 – Digital Indicator

- Min/max value memory and display
- Hold function
- Taring function for weighing applications
- Customer-specific linearization (40 value pairs or polynomial)
- Timer function
- 4 limit value monitoring functions
- Individual user level
- Separate application using structured text (ST code; optional)
- Math and logic function (optional)
- Fast wiring through PUSH IN technology
- Analog output (optional)
- RS485 interface (optional)
- Additional analog and digital inputs via RS485 interface



### Order details

<b>(1) Basic type</b>	
701510	JUMO diraVIEW 132 (size 48x24 mm, 1x analog input, 1x relay, 1x DI, 1x DI/DO)
701511	JUMO diraVIEW 116 (size 48x48 mm, 1x analog input, 2x relay, 1x DI, 1x DI/DO)
701512	JUMO diraVIEW 108 (size 48x96 mm, 1x analog input, 2x relay, 1x DI, 1x DI/DO)
701513	JUMO diraVIEW 108 (size 96x48 mm, 1x analog input, 2x relay, 1x DI, 1x DI/DO)
701514	JUMO diraVIEW 104 (size 96x96 mm, 1x analog input, 2x relay, 1x DI, 1x DI/DO)
<b>(2) Version</b>	
8	Standard with default settings
9	Customer-specific configuration (specification in plain text)
<b>(3) Option 1</b>	
0	Not to be used
1	1 relay output (make contact)
2	1 logic output 0/14 V
4	1 interface RS485
<b>(4) Option 2</b>	
0	Not to be used
1	1 relay output (make contact)
2	1 logic output 0/14 V
3	1 analog output (configurable)
7	1 Ethernet interface
<b>(5) Option 3</b>	
0	Not to be used
1	1 relay output (make contact)
2	1 logic output 0/14 V
5	1 PhotoMOS relay
<b>(6) Option 4</b>	
0	Not to be used
1	1 relay output (make contact)
2	1 logic output 0/14 V
5	1 PhotoMOS relay
6	1 relay with longer contact operating life
<b>(7) Voltage supply</b>	
23	AC 110 to 240 V +10/-15 %,48 to 63 Hz
25	AC/DC 20..30V,48..63Hz
<b>(8) Extra codes</b>	
000	Without approval
049	With BV approval
062	With DNV GL approval
214	Math and logic module
221	Structured text

**Order code**

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)

List extra codes in sequence and separate using commas.

**Important information:**

The options cannot be retrofitted! Please consider options when ordering.


**Stock versions**

Order code	Part no.
701510/8-0000-23/000	00694781
701510/8-0000-25/000	00694782
701511/8-0000-23/000	00694784
701513/8-0000-23/000	00694785
701513/8-0000-25/000	00694786
701513/8-0300-23/000	00694787
701514/8-0000-23/000	00694788

**Accessories**

Description	Part no.
USB cable, A connector to Micro-B connector length 3 m	00616250
Mounting for DIN rail, for type 702110	00688236
Mounting for DIN rail, for type 702111	00688237
Retaining bracket for DIN rail, for type 703054 (96 mm × 96 mm)	00754309
Stainl. steel housing cutout 96 x 96 mm	00628452
surface-mounting 2FGE-125-2/125 Feldgehaeuse	00361257
70211x(70151x)/214 (math and logic module)	00689708
70211x(70151x)/221 (structured text)	00689709

**Software**

Description	Part no.
Setup JUMO diraTRON 104/108/116/132	00678822