

## JUMO miroVIEW – Smart Digital Indicator with Limit Value Monitoring



- Integrated timer function
- Service and operating hours counter
- Bluetooth (option)
- Fast wiring through PUSH IN technology
- High-quality display and intuitive operation
- Configuration on the device or with the setup program (accessories) through USB interface (USB powered)
- Operator guidance with text support in 4 languages
- Limit value monitoring function

### Order details

<b>(1) Basic type</b>	
701580	JUMO miroVIEW mit 2 Relais, 76x36x62 mm
<b>(2) Version</b>	
0	Standard version
2	Customer-specific software
<b>(3) Input</b>	
01	1 RTD temperature probe Pt100, Pt1000 in 2-wire circuit, 1 digital input
02	1 RTD temperature probe Pt100, Pt1000 in 3-wire circuit
04	1 thermocouple and 1 digital input
05	0(4) to 20 mA and 1 digital input
06	0 to 10 V and 1 digital input
<b>(4) Output</b>	
23	1 relay (changeover contact AC 250 V, 10 A) and 1 relay (NO contact AC 250 V, 5 A), resistive load
26	1 relay (NO contact AC 250 V, 10 A), resistive load and 1 digital output DC 0/14 V
<b>(5) Voltage supply</b>	
02	AC 230 V +10 / -15 %, 48...63 Hz
05	AC 115 V +10 / -15 %, 48...63 Hz
30	DC 12 to 24 V +15/-15 %

### Order code

(1) (2) (3) (4) (5)  
 /  -  -  -

### Stock versions

Order code	Part no.
701580/0-01-23-02/000	30047356
701580/0-01-23-30/000	30047357
701580/0-04-23-02/000	30047361
701580/0-05-23-02/000	30047363

### Accessories

Description	Part no.
USB cable, A connector to Micro-B connector length 3 m	00616250
mounting bracket f. DIN-rail 76mm x 36mm	00483019
Activation PID two-state controller	30058739

### Software

Description	Part no.
Setup JUMO miroTRON/miroVIEW	00777355