



Screw-In Thermocouples with Terminal Head Form B (901020)

- For temperatures from -200 to +800 °C
- Available with different thermocouples
- As single or double thermocouple
- Terminal head form B, BUZ, BUZH, BBK
- Available with transmitter



Order details

		(1) Basic type		
		901020/10	Screw-in thermocouple with terminal head Form B, extension tube and continuous protection tube	
		901020/20	Screw-in thermocouple with terminal head Form B, without extension tube and continuous protection tube	
		(2) Operating temperature in °C		
X	X	150	-200..600°C	
X	X	165	-200..800°C	
		(3) Measuring insert		
X	X	1040	1x Fe-CuNi "J"	
X	X	1042	1x Fe-CuNi "L"	
X	X	1043	1x NiCr-Ni "K"	
X	X	2040	2x Fe-CuNi "J"	
X	X	2042	2x Fe-CuNi "L"	
X	X	2043	2x NiCr-Ni "K"	
		(4) Diameter prot. tube		
X	X	9,00	9 mm	
		(5) Insertion length		
X	X	160,00	160 mm	
X	X	200,00	200 mm	
X	X	250,00	250 mm	
X	X	300,00	300 mm	
X	X	400,00	400 mm	
X	X	600,00	600 mm	
X	X	100,00 - 1000,00	100 - 1000 mm	
		(6) Process connection		
X	X	104	Screw connection G 1/2	
X	X	105	Screw connection G 3/4	
X	X	106	Screw connection G 1	
X	X	126	Screw connection M18 x 1,5	
		(7) Extra codes		
X	X	000	Without extra code	
X		306	Support tube 70mm	
X	X	658	SIL- and PL-suitable with safety temperature limiter and safety temperature monitor 70115X	
X	X	659	SIL- and PL-suitable (only in connection with temperature transmitter T06, data sheet 707071)	
X	X	969	mit Prüfloch	
X		1160	H2 ready - mobile hydrogen applications	
X	X	320	Terminal head form BUZ	
X	X	321	Terminal head form BUZH	
X	X	322	Terminal head form BBK	
X	X	331	1x programmable transmitter, 4 to 20 mA/20 to 4 mA output, data sheet 707010	
X	X	335	2x programmable transmitter, 4 to 20 mA/20 to 4mA output, data sheet 707010	
X	X	550	1x transmitter programmable, 4 to 20 mA/20 to 4 mA output (USB), data sheet 707050	
X	X	859	1x Wtrans B programmable transmitter with transmission, data sheet 707060	

Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Quantity discount:

As of 5 pieces: 5 %

As of 10 pieces: 10 %

As of 25 pieces: please inquire

For extra code transmitter please specify measuring range and, if applicable, output signal in plain text.


Accessories

Description	Part no.
PC interface with converter USB/TTL	00456352
Battery SL-760/S in foil bag 707060	00547559
Activation for OnlineChart	00549188
USB cable, A-connector to Mini-B connect length 3 m	00506252

Accessories see price sheet:

- Screw-In Thermowells (909710)
- Welding Protective Sleeves (909710)
- Measuring Inserts for Screw-In Thermocouples with Form B Terminal Head (909740)

Software

Description	Part no.
Setup-Program Wtrans	00488887
Setup program Wtrans inkl OnlineChart	00549067
Setup JUMO dTRANS T05 707050/51	00574959
JUMO setup dTRANS T01J 315.01.xx/1.08J	00605080