



Screw-In Thermocouples with Form J Terminal Head (901030)

- For temperatures from -200 to +800 °C
- As single or double thermocouple
- Assembly insulated or connected with protection tube
- Protection type IP65



Order details

		(1) Basic type		
		901030/10	Screw-in thermocouple with terminal head Form J and continuous protection tube	
		901030/20	Screw-in thermocouple with terminal head Form J, continuous protection tube and union nut	
			(2) Operating temperature in °C	
X	X	130	-200..400°C	
X	X	150	-200..600°C	
X	X	165	-200..800°C	
			(3) Measuring insert	
X	X	1040	1x Fe-CuNi "J"	
X	X	1042	1x Fe-CuNi "L"	
X	X	1043	1x NiCr-Ni "K"	
X	X	2040	2x Fe-CuNi "J"	
X	X	2042	2x Fe-CuNi "L"	
X	X	2043	2x NiCr-Ni "K"	
			(4) Diameter prot. tube	
X	X	6,00	Ø 6 mm	
			(5) Insertion length	
X		50,00	50mm	
X		75,00	75mm	
X		100,00	100mm	
X	X	150,00	150mm	
X	X	200,00	200mm	
X	X	250,00	250mm	
X	X	300,00	300mm	
X	X	50,00 - 600,00	50 - 600mm	
			(6) Process connection	
X		102	Screw connection G 1/4	
X		103	Screw connection G 3/8	
X		104	Screw connection G 1/2	
	X	164	Union nut G 1/2	
	X	165	Union nut G 3/4	
			(7) Extra codes	
X	X	000	Without extra code	
X	X	658	SIL- and PL-suitable with safety temperature limiter and safety temperature monitor 70115X	
X	X	659	SIL- and PL-suitable (only in connection with temperature transmitter T06, data sheet 707071)	
X	X	1160	H2 ready - mobile hydrogen applications	

Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)

Quantity discount:

As of 5 pieces: 5 %

As of 10 pieces: 10 %

As of 25 pieces: please inquire

**Stock versions**

Order code	Part no.
901030/10-150-1042-6-100-104/000	00407109
901030/10-150-1042-6-200-104/000	00520186

Accessories see price sheet:

- Screw-In Thermowells (909710)