

JUMO FOODtemp Insertion Thermocouple (901350)

- For temperatures between -100 to +260 °C
- Steam-tight
- High mechanical strength
- For use in the food industry
- Available with multiple measuring points



Order details

(1) Basic type			
	901350/33	Insertion thermocouple with multiple measuring points, PTFE handle dia.12mm and PTFE cable	
	901350/63	Insertion thermocouple with multiple measuring points, PTFE handle dia.15mm and PTFE cable	
	901350/83	JUMO FOODtemp Insertion thermocouple with multiple measuring points, angled PEEK handle and PTFE cable	
	901350/84	Insertion thermocouple with multiple measuring points, PEEK handle and PTFE cable	
	(2) Operating temperature in °C		
X	X	X	X
	261	-100..260°C	
	(3) Measuring insert		
X	X	X	X
	3043	3x NiCr-Ni "K"	
X	X	X	X
	4043	4x NiCr-Ni "K"	
X	X		
	5043	5x NiCr-Ni "K"	
	(4) Diameter prot. tube		
X	X	X	X
	4,00	Ø 4,0mm	
X	X		
	4,50	Ø 4,5mm	
	(5) Insertion length		
X	X	X	X
	100,00	100,0	
X	X	X	X
	150,00	150,0	
X	X	X	X
	200,00	200,0	
	(6) Insertion tip		
X	X	X	X
	2	centric, angle 25°	
X	X	X	X
	3	bevel, angle 45°	
	(7) Connecting cable end		
X	X	X	X
	03	Stripped cable ends	
X	X	X	X
	11	Ferrules	
X	X	X	X
	80	Multipole connector (type indicated in plain text)	
	(8) Connecting line length in mm		
X	X	X	X
	4000	4000 mm	
X	X	X	X
	500 - 500000	Indication in plain text (gradation 500mm)	
	(9) Extra codes		
X	X	X	X
	000	Without extra code	
X	X	X	X
	658	SIL- and PL-suitable with safety temperature limiter and safety temperature monitor 70115X	
X	X	X	X
	659	SIL- and PL-suitable (only in connection with temperaturetransmitter T06, data sheet 707071)	

Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)

Quantity discount:

As of 5 pieces: 5 %

As of 10 pieces: 10 %

As of 25 pieces: please inquire

