

## JUMO HEATtemp – Screw-In RTD Temperature Probe for Combined Cold/Heat Meters with Terminal Head for Direct Installation, Type DL (902454)



### Order details

		<b>(1) Basic type</b>	
		902454/10	Screw-in RTD temperature probe with terminal head form B (standard) and continuous protection tube, design type DL
		902454/11	Screw-in RTD temperature probe with terminal head form B (standard) and stepped protection tube, design type DL
		<b>(2) Operating temperature in °C</b>	
X	X	818	0..120°C
		<b>(3) Measuring insert</b>	
X	X	1003	1x Pt100 in 2-wire circuit
X	X	1004	1x Pt500 in 2-wire circuit
X	X	1005	1x Pt1000 in 2-wire circuit
X	X	1011	1x Pt100 in 4-wire circuit
X	X	1012	1x Pt500 in 4-wire circuit
X	X	1013	1x Pt1000 in 4-wire circuit
		<b>(4) Tolerance class</b>	
X	X	1	Class B
X	X	2	Class A
X	X	3	Class AA
		<b>(5) Diameter prot. tube</b>	
X		6,00	6 mm
	X	8,00	8 mm
		<b>(6) Insertion length</b>	
X	X	85,00	85 mm
X	X	120,00	120 mm
X	X	155,00	155 mm
X	X	210,00	210 mm
X	X	85,00 - 400,00	85 to 400 mm
		<b>(7) Process connection</b>	
X	X	104	Screw connection G 1/2
		<b>(8) Extra codes</b>	
X	X	000	Without extra code
X	X	340	Version paired according to EN 1434 up to 150°C
X	X	341	Version paired according to EN 1434 and certified <sup>1 2</sup>
X	X	761	Version paired with CE- and metrology labeling (first calibration) <sup>2</sup>

### Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)



Accessories see price sheet:

- Installation Location and Accessories for Temperature Probes (902442)
- Terminal Heads (909715)

