


Level and Temperature Probe for Utility Vehicles as Well as Construction and Agricultural Machinery (902880)

- For temperatures from -40 to +140 °C
- As level or combined level and temperature probe
- Connecting cable: cross-linked polyester
- Installation position: standing or suspended
- Measuring path of 50 mm or 62 mm



Order details

		(1) Basic type	
	902880/10	Level and temperature probes for utility vehicles as well as construction and agricultural machinery	
		(2) Operating temperature in °C	
X	481	-40..140°C max. (1h) 150°C	
		(3) Measuring path	
X	50	50 mm	
X	62	62 mm	
		(4) Measuring insert	
X	0000	Without measuring insert	
X	1003	1x Pt100 in 2-wire circuit	
X	1004	1x Pt500 in 2-wire circuit	
X	1005	1x Pt1000 in 2-wire circuit	
X	9999	According to customer specifications	
		(5) Diameter prot. tube	
X	12,00	12mm	
		(6) Insertion length	
X	110,00	110mm	
X	140,00	140mm	
X	170,00	170mm	
X	180,00	180mm	
X	200,00	200mm	
X	220,00	220mm	
		(7) Process connection	
X	133	Screw connection M24 x 1,5	
X	999	According to customer specifications	
		(8) Connecting cable end	
X	03	Stripped cable ends	
X	79	Bayonet lock DIN 72585	
X	99	According to customer specifications	
		(9) Connecting line length in mm	
X	110	110 mm	
X	400	400 mm	
X	550	550 mm	
X	1000	1000 mm	
X	110 - 10000	Indication in plain text (gradation 50mm) (price for 10 mm AL each)	
		(10) installation position	
X	1	standing (process connection in medium)	
X	2	suspended (process connection not in medium)	
		(11) Extra codes	
X	000	Without extra code	
X	852	PA 6 corrugated hose over connecting cable	

Order code

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
<input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	/ <input type="text"/>

Quantity discount:

As of 5 pieces: 5 %

As of 10 pieces: 10 %

As of 25 pieces: please inquire

