

## JUMO Wtrans E01 - Measuring Probe for Humidity, Temperature, and CO<sub>2</sub> with Wireless Data Transmission (902928)

- Humidity from 0 to 100 % RH (incl. -40 to +80 °C) or CO<sub>2</sub> from 0 to 2000/5000/10000 ppm or temperature from -200 to +600 °C using Pt1000 RTD temperature probe
- Two inputs for measured value recording
- Wall-mounted housing with backlit LCD display
- Open air range 300 m
- Wiring expenses are eliminated with modern wireless technology



### Order details

|                       |  |
|-----------------------|--|
| <b>(1) Basic type</b> |  |
| 902928/10             | Wtrans E01 measuring probe for humidity, temperature and CO <sub>2</sub> with wireless data transmission |
| <b>(2) Version</b>    |  |
| 8                     | Standard with default settings   |
| 9                     | Customer-specific configuration (specification in plain text)  |
| <b>(3) Parameter</b>  |  |
| 10                    | Humidity, temperature and CO <sub>2</sub> (standard)   |
| 20                    | Activation of further parameters   |

### Order code

(1) (2) (3)

-  -



### Stock versions

| Order code         | Part no. |
|--------------------|----------|
| 902928/10-8-10/000 | 00618852 |

**Accessories**

| Description   | Part no. |
|---|----------|
| Activation for OnlineChart  | 00549188 |
| USB cable, A-connector to Mini-B connect length 3 m   | 00506252 |
| Add.lambda/4 antenna 868MHz 120°C   | 00503151 |
| Wall holder with counterweight for lambd  | 00482648 |
| Antenna cable, L 3 m, impedance 50 Ohm  | 00601189 |
| Antenna cable, L 5 m, impedance 50 Ohm  | 00601190 |
| Antenna cable, L 10 m, impedance 50 Ohm   | 00669026 |
| Lithium-battery 4x 1,5 V (size AA) blister packaging  | 00617446 |
| Battery holder 4x 1,5 V   | 00606043 |
| CON Printklemme 2pol picoMAXeCOM 5. Anschlussklemme   | 00598340 |
| Steckernetzteil 100-240VAC fuer WtransEO<br>Steckernetzteil 9V<br>DKD<br>905021<br>90.5021<br>90.2721<br>779<br>Präzision | 00619184 |
| Modbus-Sonde(PC) mit PTFE-Filter (rF+T)   | 00614528 |
| Modbus-Sonde(PC) mit PTFE-Filter (CO2_0.  | 00614530 |
| Modbus-Sonde(PC) mit PTFE-Filter (CO2_0.  | 00614531 |
| Modbus-Sonde(PC) mit PTFE-Filter (CO2-0.  | 00614532 |
| 902815/99-370-1013-2-12-65-000-20/310   | 00606033 |
| 902150/99-386-1013-2-6-100-56-2500/315  | 00551310 |
| 902150/99-386-1013-2-6-100-56-2500/317  | 00551311 |
| 902815/10-380-1013-2-6-100-000-24/452   | 00511233 |
| Compression Fitting G1/2 D=6mm SS<br>Klemmverschraubung<br>Verschraubung  | 00305445 |
| Compression Fitting G1/2 D=12mm SS  | 00312448 |
| Rohrverschr. M 20x1,5<br>Klemmverschraubung   | 00558447 |
| Kabelverschraubung M20 x 1,5 (CuZn vni)<br>Verschraubung  | 00575665 |
| SET Wall holder Wtrans probe protection   | 00503329 |
| SET Wall holder Wtrans probe protection   | 00503328 |
| SAC-5P-M12MS/2,0-PUR/M12FS SH5  | 00503577 |
| SAC-5P-M12MS/5,0-PUR/M12FS SH5  | 00503578 |
| SAC-5P-M12MS/10,0-PUR/M12FS SH5   | 00503579 |
| preconfiguration (Service)  | 00427968 |
| deployment of service   | 00427970 |

**Software**

| Description                           | Part no. |
|---------------------------------------|----------|
| Setup-Program Wtrans                  | 00488887 |
| Setup program Wtrans inkl OnlineChart | 00549067 |