

## JUMO plastoSENS T03 – Steam-Tight Plastic Temperature Probe (904003)

- For temperatures from 0 to 150 °C
- Protection type IP69K – steam-tight even at the cable outlet
- Absolute leak-tightness – through injection molding process the applied special plastics form a substance-to-substance bond which guarantees the steam tightness
- Application areas: autoclaves, steam sterilizers, CIP and SIP cleaning (depending on the type of applied chemicals)



### Order details

|   |   |   |   |
|---|---|---|---|
|   |   | <b>(1) Basic type</b>                   |   |
|   |   | 904003/10                               | TPE-S/TPE-S, 5,4 x 35 mm, IP68                  |
|   |   | 904003/20                               | TPE-S/TPE-S, 6,9 x 50 mm, IP68                  |
| X | X | <b>(2) Operating temperature in °C</b>  |   |
|   |   | 824                                     | 0..150°C  |
| X | X | <b>(3) Measuring insert</b>             |   |
|   |   | 2001                                    | 2x Pt100 in 3-wire circuit                      |
|   |   | 2005                                    | 2x Pt1000 in 2-wire circuit                     |
| X | X | <b>(4) Tolerance class</b>              |   |
|   |   | 2                                       | Class A   |
| X | X | <b>(5) Connecting cable end</b>         |   |
|   |   | 11                                      | Ferrules  |
| X | X | <b>(6) Connecting line length in mm</b> |   |
|   |   | 2500                                    | 2500mm  |
| X | X | 500 - 10000                             | Specifications in plain text (gradation 500 mm) |

### Order code

(1) (2) (3) (4) (5) (6)

-  -  -  -  -

### Order details

Please note that not all feature combinations directly generate deliverable products. They merely describe production-based versions that are possible. Due to the special manufacturing conditions the minimum order quantity for non-standard versions is 500 pieces.