

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



JUMO variTRON 500 touch – Automation System

Central Processing Unit 705004

Brief description

The JUMO variTRON 500 touch is a central processing unit with integrated TFT color screen for operation and visualization using CODESYS TargetVisu. Along with the proven input and output modules (incl. controller module), a complete automation system can be realized.

The central processing unit manages all configuration and parameter data of the overall system and makes a PLC according to IEC 61131-3 (CODESYS V3.5) available (extra code 224).

The PLC can be activated in different versions:

- CODESYS runtime system incl. TargetVisu and/or
- Remote TargetVisu (extra code 280) and/or
- WebVisu (extra code 281)

Commercially available panels that support the TargetVisu or WebVisu functionality can be used for visualization. "Remote Target Visu" is required so that the central processing unit can provide the screen for the panel with "Remote Target Visu". Visualization is also possible via web browser. Visualizations have to be implemented with CODESYS resources.

With system version 9, the software was expanded to include visualization of the process data as a curve diagram, both on the HMI and on the web (extra code 276 "recorder app").

An easy-to-use setup program is used for configuration. JUMO standard functions for CODESYS are provided in libraries and can be individually integrated into the customer application.




Type 705004/2



Type 705004/3

Block diagram



Features

- Process mapping for all connected input/output modules (including controller module)
- Recorder app (via integrated touch panel and web, as of system version 9)
- Program app (incl. JUMO variTRON Template, as of system version 8.2)
- Wireless interface for Wtrans transmitters
- PROFINET IO-Controller/Device (in conjunction with PLC, Device as of system version 8.2)
- Battery-buffered SRAM (synchronization of retain data in CODESYS application)
- Data evaluation with JUMO smartWARE Evaluation

Approvals and approval marks (see technical data)



JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD

JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



Description

JUMO variTRON 500 touch

The JUMO variTRON 500 touch central processing unit is based on the new hardware platform. It is equipped with an 800 MHz processor, which is used as a quad-core variant.

The JUMO variTRON 500 touch central processing unit is integrated into the housing of a TFT color screen, which is used for operation and visualization (capacitive touchscreen). It is available in screen sizes of 7 inches and 10.1 inches. Both sizes are also available with stainless steel front.

Due to the scalability of hardware and software, a modular, flexible, and above all sustainable hardware platform is available that is combined with a modern software architecture. Based on this new platform, innovative operating concepts can now be implemented using state-of-the-art display technologies.

The advantages at a glance:

- High speed performance
- Flexible operating philosophy
- Modern communication interfaces (e.g. OPC UA, MQTT)
- Integration of different fieldbus protocols such as PROFINET IO, EtherCAT, and Modbus-TCP/RTU
- Easy integration of new software functions via PLC (CODESYS V3.5)
- Availability of function and visualization libraries (as of system version 6)
- Easy adaptation of hardware inputs and outputs
- Customer-specific operation and visualization with several operator stations via CODESYS remote target visualization or via web visualization (mixed operation is possible)
- Panels in various formats (portrait or landscape, 4:3 or 16:9)
- JUMO Web Cockpit
- Recorder app for recording and visualizing process data

Input/output modules

Both the JUMO variTRON input and output modules (7050xx series) and the JUMO I/O system modules (7051xx series) are available as module variants.

For example: the analog input module with universal inputs for thermocouples, RTD temperature probes, and voltage or current standard signals. As a result, the same hardware can be used to precisely acquire and digitize a highly diverse range of process variables.

The mounting of the modules is possible in two variants. In variant 1, a DIN rail (accessory) is attached to the back cover of the central processing unit JUMO variTRON 500 touch, on which the modules are mounted. In variant 2, the modules are mounted on a separate DIN rail. In both variants, the connection to the central processing unit is established via a router module using a commercially available network cable (see Technical data or Accessories). The voltage for the modules is also supplied at the router module.

JUMO variTRON 500 touch enables simultaneous operation of more than 120 control loops so that it can also be used for sophisticated processes. Through expansion slots the inputs and outputs of each controller module can be individually expanded and adapted. The control loops here operate fully independently, which means they do not require resources from the central processing unit.

Thyristor power controllers can also be connected via EtherCAT or PROFINET. In addition, JUMO digiLine sensors for liquid analysis can be connected to the central processing unit.

Wireless measured value transmission

The central processing unit JUMO variTRON 500 touch is also available with a wireless interface that enables wireless transmission of measured values. The transmitters of the JUMO Wtrans series are available as measuring probes (Wtrans T, Wtrans B, Wtrans p, Wtrans E01). A maximum of 32 transmitters can be operated on the central processing unit.

During startup, the display of the RSSI value (Received Signal Strength Indicator) in the Web Cockpit is helpful as an indicator of the signal strength of a received radio telegram.

Recorder – recording of process data

The JUMO variTRON 500 touch central processing unit has a function for acquiring process data as a standard feature. This allows up to 240 analog or digital channels (signals) to be logged. The channels are combined into groups for this purpose.

By grouping the channels, the user can, for example, create a separate group for each plant or log signals with a different memory cycle. The grouping of channels is also the basis for acquiring batches.

The process data is stored in the central processing unit before this data is transferred to the Datastore for storage. The Datastore is part of the JUMO smartWARE Evaluation soft-

ware, which is used to visualize and evaluate the data. A fee-based license is required for this purpose.

Recorder app – recording and visualization of process data (extra code 276)

As of system version 9, the JUMO variTRON 500 touch central processing unit has the recorder app when extra code 276 is activated. This enables visualization of the process data as a live trend in the curve diagram (Recorder View).

The recorder app can be visualized via the integrated touch panel as part of the hybrid UI. It is also available on the web.

Hybrid UI

The hybrid UI (user interface) is a combination of firmware and CODESYS visualization in one device. The hybrid UI makes operation easier and increases user-friendliness.

Acquisition of batches

The scope of the JUMO variTRON 500 touch central processing unit also includes the acquisition of batches. As a result, up to 20 batches can be logged simultaneously.

The batch data is acquired together with the channels (signals) of the assigned groups and the event messages.

The batches are also only temporarily stored in the central processing unit. Storage, visualization, and evaluation are then carried out with the JUMO smartWARE Evaluation software. A fee-based license is also required for this purpose (number of batches).

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD

JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



JUMO Cloud

The IoT platform for process visualization as well as data acquisition, evaluation, and archiving enables worldwide access to measurement data using common web browsers. The JUMO Cloud is characterized by a high degree of security as well as valuable visualization, alarm, and planning functions.

Further information on the JUMO Cloud:

qr-en-cloud.jumo.info

JUMO smartWARE SCADA

The JUMO smartWARE SCADA software provides easy access to measurement data using conventional web browsers. It offers functions for process visualization as well as for evaluation of the acquired data. The software also supports manufacturing and work processes with valuable visualization, alarm, and planning functions.

Further information on the JUMO smartWARE SCADA software:

qr-en-scada.jumo.info

JUMO smartWARE Evaluation

JUMO smartWARE Evaluation is intended for evaluating and visualizing process data from the JUMO variTRON system. The process data can be evaluated in customizable dashboards based on time or batch and transferred into reports (e.g. PDF, Excel®, CSV).

Further information on the JUMO smartWARE Evaluation software:

qr-en-evaluation.jumo.info

JUMO variTRON Program App

The browser-based software solution JUMO variTRON Program App enables intuitive creation and editing of process technology programs and recipes on the JUMO variTRON 500 and the JUMO variTRON 500 touch via web access. As a result, plant manufacturers can define process steps and then link them into a program using the graphical editor. The plant user can control the program sequence via a connected web interface.

Further information about the JUMO variTRON Program App software:

qr-en-program.jumo.info

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Technical data

Interfaces

USB host Designation Type Number Device category Application Data rate Max. current	USB A (socket) 2 Mass Storage Class, Communications Device Class – Ethernet Control Module Connecting a USB flash drive or a USB to Ethernet converter Low Speed, Full Speed, Hi-Speed 500 mA per interface
Ethernet Designation Type Number Protocol Application Transfer rate Connecting cable Cable length	LAN1, LAN2, LAN3 (optional) RJ45 2 (optional: 3) TCP, IPv4, HTTP(S) Via CODESYS as an option: Modbus TCP, PROFINET IO controller/device (device as of system version 8.2), EtherCAT master, OPC UA server, BACnet/IP Communication with: - PC (setup program, web browser) - email server - Modbus TCP master/slave - PROFINET IO device/controller - EtherCAT slave - OPC UA client - BACnet/IP server/client - JUMO system bus via JUMO variTRON router modules (LAN1 only) 10 Mbit/s, 100 Mbit/s (EtherCAT: 100 Mbit/s) Network cable, at least CAT5e (S/FTP) Up to 100 m
RS485 (serial interface) Designation Type Number Application Protocol Data format Transfer rate	COM Terminal strip 2-pole 1 Fieldbus applications, communication via modem with a PC or with an email server Via CODESYS: Modbus RTU master/slave 8/1/n, 8/1/e, 8/1/o 9600 Bd, 19200 Bd, 38400 Bd, 115200 Bd

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Wireless interface (optional)	
Antenna connector	SMA socket
Radio frequency	868.4 MHz (Europe) or 915 MHz (USA, Australia, Canada, New Zealand ...)
	In the 915 MHz frequency band (912.6 MHz to 917.4 MHz) one of 10 fixed frequencies can be set.
Open air range	300 m with 868.4 MHz or 200 m with 915 MHz
	Range when using the antenna holder for wall mounting with 3 m long antenna cable; when mounting the antenna directly to the receiver, a reduction in the range must be taken into account.
Required RSSI value for error-free transmission	> -90 (with stationary transmitter)
	The RSSI value is an indicator of the strength of the received signal (theoretical value range: -120 to 0).
Application	Receiver for JUMO Wtrans transmitters (wireless measured value transmission)
Compatible transmitters	Wtrans T (902930), Wtrans B (707060), Wtrans p (402060), Wtrans E01 (902928)
	Not supported thermocouple types with Wtrans B: MoRe5-MoRe41, W3Re-W26Re

Screen

Type	TFT color screen
Touch technology	Capacitive
Screen size (diagonal)	
Types 705004/0, 705004/1	Approx. 17.8 cm (7")
Types 705004/2, 705004/3	Approx. 25.7 cm (10.1")
Resolution	
Types 705004/0, 705004/1	1024 × 600
Types 705004/2, 705004/3	1280 × 800
Number of colors	16.7M
Brightness (luminance)	Typically 400 cd/m ²
Backlight	LED (dimnable in 7 steps)


JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Electrical data

Voltage supply Symbol (see nameplate) Connection Voltage Residual ripple	 Removable terminal strip 3-pole with push-in technology (incl. connection for functional ground) DC 24 V +25/-20 % SELV 5 %
Current consumption Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	(at DC 19.2 V) Max. 0.84 A Max. 0.84 A Max. 0.91 A Max. 0.91 A
Power consumption Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	Max. 17.5 W Max. 17.5 W Max. 19.4 W Max. 19.4 W
Conductor cross section (terminals +24V, GND, FE) Wire or stranded wire without ferrule Stranded wire with ferrule 2 × stranded wire with twin ferrule with plastic collar Stripping length	Min. 0.2 mm ² , max. 2.5 mm ² Min. 0.25 mm ² , max. 2.5 mm ² Min. 0.5 mm ² , max. 1.5 mm ² 10 mm
Conductor cross section COM (terminals 1, 2) Wire or stranded wire without ferrule Stranded wire with ferrule Stripping length	Min. 0.14 mm ² , max. 1.5 mm ² Without plastic collar: min. 0.25 mm ² , max. 1.5 mm ² With plastic collar: min. 0.25 mm ² , max. 0.5 mm ² 9 mm
Electrical safety	According to DIN EN 61010-1:2020 Overvoltage category III, pollution degree 2
Protection rating	III
Electromagnetic compatibility Interference emission Interference immunity	According to DIN EN 61326-1:2022 Class A – only for industrial use – Industrial requirement
Radio frequency spectrum 868.4 MHz 915 MHz (912.6 MHz to 917.4 MHz)	According to ETSI EN 300 220-1 and ETSI EN 300 220-2 According to FCC - Title 47 CFR Part 15 and ANSI C63.4
Data backup	Buffered RAM
Buffer battery service life	Typically 6 years (lithium battery CR2032) Observe fault messages on battery status in the event list (battery almost empty, battery empty)!

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Housing and environmental conditions

Case type Types 705004/0, 705004/2 Types 705004/1, 705004/3	Housing for installation in panel cut-out (indoor use), horizontal orientation only Plastic housing, display with glass front Plastic housing with stainless steel front (V2A), display with glass front
Front panel (width × height) Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	199.7 mm × 134.7 mm 229 mm × 164 mm 265.1 mm × 180.5 mm 294.4 mm × 209.8 mm
Thickness of the front frame (without seal) Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	8.1 mm 5.5 mm 8.1 mm 5.5 mm
Mounting depth (up to seal) Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	(without DIN rail) 49.6 mm (shallower housing), 58.7 mm (deeper housing) 53.6 mm (shallower housing), 62.7 mm (deeper housing) 49.6 mm (shallower housing), 58.7 mm (deeper housing) 53.6 mm (shallower housing), 62.7 mm (deeper housing)
Panel cut-out (width×height) Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	190.2 mm × 125.2 mm (+ 1 mm) 214 mm × 149 mm (+ 1 mm) 253 mm × 168.4 mm (+ 1 mm) 279.4 mm × 194.8 mm (+ 1 mm)
Panel thickness Types 705004/0, 705004/2 Types 705004/1, 705004/3	Max. 7 mm Max. 8 mm
Weight (fully fitted) Type 705004/0 Type 705004/1 Type 705004/2 Type 705004/3	Approx. 1020 g Approx. 1810 g Approx. 1440 g Approx. 2430 g
Protection type Types 705004/0, 705004/2 Types 705004/1, 705004/3	According to DIN EN 60529 At the front IP65, at the rear IP20 At the front IP69K (high-pressure cleaning > 70 °C only when switched off), at the rear IP20
Ambient temperature range (operation) Types 705004/0, 705004/1 Types 705004/2, 705004/3	-20 to +55 °C -20 to +50 °C
Storage temperature range	-30 to +70 °C
Resistance to climatic conditions Operation Storage	Relative humidity ≤ 90 % annual average, no condensation Climate class 3K22 according to DIN EN 60721-3-3 with extended temperature and humidity range Climate class 1K21 according to DIN EN 60721-3-3 with extended temperature and humidity range
Site altitude	Up to 2000 m above sea level
Oscillation Amplitude Acceleration	According to DIN EN 60068-2-6, table C.2 0.15 mm from 10 to 58.1 Hz 20 m/s ² from 58.1 to 150 Hz

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Shock	According to DIN EN 60068-2-27, table A.1
Peak acceleration	150 m/s ²
Shock duration	11 ms
Degree of protection against mechanical loads (shock resistance)	According to DIN EN 50102/A1
Types 705004/1, 705004/3	IK08 (shatterproof)

Approvals and approval marks

c UL us	
Test facility	Underwriters Laboratories
Certificate/certification number	E201387
Inspection basis	UL 61010-1 (3. Ed.), CAN/CSA-22.2 No. 61010-1 (3. Ed.)
Valid for	All types without DIN rail on the rear side

NEMA 4X	
Test facility	Keystone Compliance, LLC.
Certificate/certification number	2310-272N
Inspection basis	NEMA 250
Valid for	Variant with stainless steel front

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk


JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Connection diagram

The connection diagram in the data sheet provides information on product selection.

For the electrical connection, only use the installation instructions or the operating manual.



- 1 Voltage supply and functional ground
- 2 Interface LAN3 (Ethernet), optional
- 3 Interface LAN2 (Ethernet)
- 4 Interface LAN1 (Ethernet/JUMO system bus)
- 5 2 USB host interfaces
- 6 Interface COM (RS485)
- 7 Antenna connector for wireless interface, optional

Interfaces


Connection	Product name	Number	Connection element	Assignment
USB host (2 ×)	USB	(5)	USB socket type A (2 ×)	
Ethernet	LAN1	(4)		1 TX+ Transmission data +
	LAN2	(3)		2 TX- Transmission data -
	LAN3 (optional)	(2)		3 RX+ Received data + 6 RX- Received data -
Serial interface RS485	COM	(6)	Terminal strip 2-pole	1 TxD+/RxD+ Transmission/received data + 2 TxD-/RxD- Transmission/received data -
Antenna		(7)	SMA socket	

Voltage supply

Connection	Product name	Number	Symbol and terminal designation
Voltage supply In	+24 V and GND	(1)	
Functional ground			



Electrical isolation




1 Functional galvanic isolation for connection of SELV or PELV electrical circuits.

Control elements

Front

Touch operation (depending on application)

Back cover



- 1 Nameplate
- 2 SMA antenna screw connection
- 3 Buffer battery compartment
- 4 Switches for terminating resistors (RS485)
- 5 COM port
- 6 2 Type A USB ports
- 7 RJ45 LAN1, LAN2 connections; LAN3 optional
- 8 DC 24 V voltage supply connection
- 9 Reset push-button (resetting to default settings)

JUMO GmbH & Co. KG
Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net




JUMO UK LTD
JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.
6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



Dimensions

705004/0 (shallower housing)






JUMO GmbH & Co. KG
Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD
JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.
6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



705004/0 (deeper housing)






JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



705004/1 (shallower housing)






JUMO GmbH & Co. KG
Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD
JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.
6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



705004/1 (deeper housing)






JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



705004/2 (shallower housing)






JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



705004/2 (deeper housing)






JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



705004/3 (shallower housing)






JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



705004/3 (deeper housing)



JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD

JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



Module overview

Central processing unit

- JUMO variTRON 500 touch, Data sheet 705004

Input/output modules

- Multichannel controller module, Data sheet 705010
- Relay module 4-channel, Data sheet 705015
- Analog input module 4-channel, Data sheet 705020
- Analog input module 8-channel, Data sheet 705021
- Analog output module 4-channel, Data sheet 705025
- Digital input/output module 12-channel, Data sheet 705030
- Digital input/output module 32-channel, Data sheet 705031
- Thyristor power controller type 70906x, Data sheet 709061, 709062, 709063

Special modules

- Router module 2-port, Data sheet 705041
- Router module 3-port, Data sheet 705042
- Router module 1-port, Data sheet 705043

Panels

- JUMO variTRON web panels, Data sheet 705070

Power supply units

- 705090/03-33, Data sheet 705090
- 705090/05-33, Data sheet 705090
- 705090/10-33, Data sheet 705090

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Order details

(1)	Basic type
705004	Central processing unit, type 705004, integrated in the operating panel (capacitive touchscreen, 2 × Ethernet, 2 × USB host, RS485), program generator, Node-RED, math and logic module ^a , communication protocols (PROFINET IO-Controller/Device 1-Port, Modbus RTU / TCP Master/Slave, OPC UA Server, EtherCAT Master, BACnet/IP) ^c
(2)	Basic type extension 1
0	7" variant
1	7" variant with stainless steel front
2	10.1" variant
3	10.1" variant with stainless steel front
(3)	Basic type extension 2
2	Quad core CPU
(4)	Basic type extension 3
2	RAM 1024 MB
(5)	Basic type extension 4
1	eMMC 8 GB ^b
(6)	Basic type extension 5
0	Without UPS (upon request)
1	With UPS
(7)	Version
0	Standard with default settings
(8)	Interface LAN3
00	Not used
08	Ethernet (RJ45)
(9)	Wireless interface
00	Not used
10	Wtrans 868.4 MHz (Europe)
20	Wtrans 915 MHz (USA, Australia, Canada, New Zealand, etc.)
(10)	Voltage supply
36	DC 24 V +25/-20 %, SELV
(11)	Extra codes
001	JUMO variTRON Program App (incl. Template, as of system version 8.2) ^{c, d}
224	PLC according to IEC 61131-3 (CODESYS V3.5; necessary to operate the device as a PLC) ^e
276	Recorder app (as of system version 9)
280	CODESYS Remote TargetVisu ^{c, e}
281	CODESYS WebVisu ^{c, e}
290	CODESYS Remote TargetVisu (required for CODESYS visualization with the integrated touch panel) ^{c, e}

^a Activation for all connected controller modules.

^b Flexible allocation between system data and application data.

^c Only in conjunction with extra code 224.

^d Only in conjunction with extra code 281 or 290.

^e This function can be used free of charge for 30 minutes in demo mode.

Order code:

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (11)
 705004 / [] 2 2 1 [] - 0 - [] - [] - 36 / 224 , 290 , ^a

^a List further extra codes in sequence, separated by commas.

Order example:

705004 / 2 2 2 1 1 - 0 - 00 - 00 - 36 / 224 , 290

JUMO GmbH & Co. KG

Delivery address: Mackenrodtstraße 14
36039 Fulda, Germany
Postal address: 36035 Fulda, Germany
Phone: +49 661 6003-0
Fax: +49 661 6003-607
Email: mail@jumo.net
Internet: www.jumo.net

JUMO UK LTD

JUMO House
Temple Bank, Riverway
Harlow, Essex, CM20 2DY, UK
Phone: +44 1279 63 55 33
Fax: +44 1279 62 50 29
Email: sales@jumo.co.uk
Internet: www.jumo.co.uk

JUMO Process Control, Inc.

6724 Joy Road
East Syracuse, NY 13057, USA
Phone: +1 315 437 5866
Fax: +1 315 437 5860
Email: info.us@jumo.net
Internet: www.jumousa.com



Scope of delivery

1 central processing unit, type 705004, in the ordered version
1 lambda/4-antenna (only for device with wireless interface)
1 installation instructions
Mounting elements
Type 705004/0: 8 pieces (only 6 are needed)
Type 705004/1: 8 pieces
Type 705004/2: 8 pieces
Type 705004/3: 16 pieces

Stock versions

Order code	Part no.
705004/0221-0-00-00-36/224,290	30052961
705004/0221-0-00-00-36/224,283,290	30053032
705004/2221-0-00-00-36/224,283,290	30053033
705004/2221-0-08-00-36/224,290	30049514

JUMO GmbH & Co. KG
 Delivery address: Mackenrodtstraße 14
 36039 Fulda, Germany
 Postal address: 36035 Fulda, Germany
 Phone: +49 661 6003-0
 Fax: +49 661 6003-607
 Email: mail@jumo.net
 Internet: www.jumo.net

JUMO UK LTD
 JUMO House
 Temple Bank, Riverway
 Harlow, Essex, CM20 2DY, UK
 Phone: +44 1279 63 55 33
 Fax: +44 1279 62 50 29
 Email: sales@jumo.co.uk
 Internet: www.jumo.co.uk

JUMO Process Control, Inc.
 6724 Joy Road
 East Syracuse, NY 13057, USA
 Phone: +1 315 437 5866
 Fax: +1 315 437 5860
 Email: info.us@jumo.net
 Internet: www.jumousa.com



Accessories

Designation	Part no.
Extra codes (activations):	
Recorder app (as of system version 9)	30071661
JUMO variTRON Program App (incl. Template, as of system version 8.2)	00771090
PLC according to IEC 61131-3 (CODESYS V3.5; necessary to operate the device as a PLC)	00724988
Remote TargetVisu	00724990
CODESYS WebVisu	00724991
CODESYS Remote TargetVisu (required for visualization with the integrated touch panel)	30049496
USB to Ethernet converter ^a :	
TP-Link UE300 USB to Gigabit LAN Converter ^b	30047695
Network cable ^a :	
RJ45 patch cable SF/UTP, length 0.3 m	00747472
RJ45 patch cable S/FTP, Cat. 6A, length 1.5 m	00666324
RJ45 patch cable S/FTP, Cat. 6A, length 3 m	00666326
RJ45 patch cable S/FTP, Cat. 6A, length 5 m	00665966
RJ45 patch cable S/FTP, Cat. 6A, length 10 m	00666327
Accessories for wireless interface ^a :	
Antenna cable, length 1 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 85 °C	00710813
Antenna cable, length 3 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 85 °C	00482646
Antenna cable, length 5 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 85 °C	00490066
Antenna cable, length 5 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 125 °C	00660378
Antenna cable, length 10 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 85 °C	00490068
Antenna cable, length 10 m, impedance 50 ohm with preconfigured screw-type connection, T _{max.} 125 °C	00511870
Antenna holder for wall mounting with antipole for lambda/4 antenna	00482648
Lambda/4 antenna with waterproof, permanently connected cable, length 10 m, T _{max.} 125 °C	00757047
Lambda/4-antenna, impedance 50 ohm, T _{max.} 125 °C	00757039
Amplifier ZX60-0916LN, packaged (ambient temperature -25 to +125 °C)	00715285
Accessories for module mounting on the back cover of the central processing unit ^a :	
DIN rail incl. fastening material and terminal block for functional ground	30047694
Cover for system bus	30049495
Screw-on end clamp for DIN rail (2 pieces are required)	00528648
Starter kits ^c :	
JUMO variTRON 500 touch starter kit, 7" variant	
JUMO variTRON 500 touch starter kit, 10.1" variant	

^a The accessories are not part of the device approvals.

^b This USB to Ethernet converter with RTL8153 chipset has been tested by the manufacturer. Other USB to Ethernet converters with the same chipset should also be usable, as well as converters with the following chipsets: Realtek RTL8150, RTL8152, RTL8153ASIX AX88xxx based, AX88179, AX88178ASMSC LAN95XX based.

^c Ordering is only possible via the contact person at the manufacturer.