

## JUMO flowTRANS MAG H20

- Flow rates: 0.005 to 150 l/min
- Medium temperature: Up to 90 °C
- Insertion length: 110 mm
- Inlet/outlet section:  $\geq 0$  DN/ $\geq 0$  DN
- SPE with PoDL (Modbus TCP, JUMO Cloud gateway)



### Order details

|  |  |
|--|--|
| <b>(1) Basic type</b>                    |  |
| 406065                                   | JUMO flowTRANS MAG H20   |
| <b>(2) Version</b>                       |  |
| 0  | Standard version   |
| <b>(3) Nominal width</b>                 |  |
| 0006                                     | DN 6 (1/4 in.)   |
| 0015                                     | DN 15 (1/2 in.)  |
| 0020                                     | DN 20 (3/4 in.)  |
| 0025                                     | DN 25 (1 in.)  |
| <b>(4) Material measuring tube</b>       |  |
| 79                                       | PEEK   |
| <b>(5) Process connection</b>            |  |
| 32                                       | External thread ISO 228  |
| 60                                       | Tri clamp as per DIN 32676   |
| <b>(6) Material seals measuring tube</b> |  |
| 58                                       | EPDM   |
| <b>(7) Calibration</b>                   |  |
| 01                                       | Standard   |
| <b>(8) Material housing</b>              |  |
| 20                                       | Stainless steel  |
| <b>(9) Display/Operation</b>             |  |
| 01                                       | Display and Bluetooth  |
| <b>(10) Signal inputs and outputs</b>    |  |
| 11                                       | IO-Link (2 configurable: IO-Link/digital output/analog output + digital/ analog output/digital input; default: IO-Link/digital output) |
| 15                                       | SPE with PoDL (ModBus TCP Slave, JUMO Cloud Gateway)   |

### Order code

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10)

/   -  -  -  -  -  -  -  -



Single Pair Ethernet

**Accessories**

| Description  | Part no. |
|--|----------|
| 4-port SPE network switch (10BASE T1L)   | 30062113 |
| 8-port SPE network switch (10BASE T1L)   | 30062447 |
| SPE network cable 10m (with M12-connec.)                                       | 30062455 |
| SPE network cable 5m (with M12-connec.)  | 30062456 |
| SPE network cable 2m (with M12-connec.)  | 30062457 |
| SPE network cable 1m (with M12-connec.)  | 30062458 |
| SPE-plug according to IEC 63171-2 (IP20)                                       | 30062461 |
| SPE-Data Cabel 2x0,35 GY schirmed  | 30071873 |
| JUMO smartCONNECT (App)  | 00770436 |
| IO-Link Master 4 Kanal - TURCK TBEN-S2-4                                       | 00759867 |
| IO Link Master 8 channel   | 00759875 |
| USB IO-Link Master 1 Channel<br>(use with Windows-PC),<br>incl. Mini-USB-Cable | 00694070 |
| Connection cable M8/voltage 2 m<br>IO Link Master 4 channel                    | 00767913 |
| Connection cable M12/voltage 2 m<br>IO Link Master 8 channel                   | 00767914 |
| Connection cable M8/Ethernet 2m<br>IO Link Master 4 channel                    | 00767923 |
| Connection cable M12/Ethernet 2m<br>IO Link Master 8 channel                   | 00767927 |
| Connection cable M12 5-pole 2 m  | 00777804 |

**Software**

| Description                             | Part no. |
|---|----------|
| JUMO flowTRANS MAGH20 IO-Link IODD V1.1 | 30065882 |