

JUMO mTRON T - Analog Output Module Four-Channel (705025)

- Four analog outputs 0(2) to 10 V or 0(4) to 20 mA (configurable per channel)
- Configurable behavior in case of an error, e.g. acc. to NAMUR recommendation NE 43
- Automatic configuration after the module insert has been exchanged (hot swappable)
- Connection of outputs on front
- Removable terminal strips with Push-In technology
- Quick wiring of operating voltage and system bus provided by simple module connection principle



Order details

(1) Basic type	
705025	Analog output module 4-channel
(2) Voltage supply	
36	DC 24 V +25/-20 %
(3) DNV GL approved	
000	Without approval
062	With DNV GL approval

Order code

(1) (2) (3)
 / ,

Planning data: module width 22.5 mm, current consumption 220 mA



Stock versions

Order code	Basic type	Voltage supply	DNV GL approved	Part no.
705025/36/000	Analog output module 4-channel	DC 24 V +25/-20 %	Without approval	00605238

Accessories see price sheet:

- JUMO mTRON T - Central Processing Unit (705001)
- Multichannel Controller Module (705010)
- Relay Module 4-Channel (705015)
- Analog Input Module 4-Channel (705020)
- Analog Input Module 8-Channel (705021)
- Digital Input or Output Module 12-Channel (705030)
- JUMO mTRON T − Router Module (705040)
- JUMO mTRON T – Multifunction Panel 840 (705060)
- Operating Panels – for JUMO mTRON T Measuring, Control, and Automation system (705065)
- Power Supply Units – Module for Automation System (705090)